

BT-LMU-3030 Installation Using An Extender Cable (available from Btracking)

Installation Time – 3 minutes

Though the BT-LMU-3030 vehicle tracker provides a wealth of vehicle information via the OBD (On Board Diagnostics) port and is easy to install (simply plug it into the OBD port), it is visible and can be unplugged easily.

For a more discrete installation of the BT-LMU-3030 device, use an **OBD Extender Cable** available from Btracking. We carry: 12 " (30 cm) and 36" (1 m) 90 degree extenders; and 36" (1 m) 180 degree extenders.



12" (30 cm) Extender Cable with 90 degree plug

By concealing the tracker behind the dash, it is much less visible:



Without Extender Cable

Using an Extender Cable

Installing the BT-LMU-3030 Using an Extender Cable:

Plug the tracker into the female connector of the Extender Cable:



Press the Extender Cable's male connector **VERY FIRMLY** into the OBD port (located at the base of the dash next to the steering column). You should feel the connector snap into place:



Tuck the tracker and cable behind the dash (if there is a cover under the dash, you might need to open it) and secure it with a cable tie and/or electrical tape. Tracker can be oriented in any position.



IMPORTANT!

When your vehicle is serviced, the mechanic may remove the tracker from the OBD II port to perform diagnostics. Always check that the tracker has been re-plugged before leaving the garage!